

Commissioning of the Irradiated Material Characterization Laboratory

***HOTLAB 2018
September 16, 2018***

Presented by Mitch Meyer

www.inl.gov




IMCL Team

Cynthia Adkins, Jeff Bailey, Aaron Balsmeier, Jayson Bush, Miles Cook, Emil Franklin, Jian Gan, Jeff Giglio, Lingfeng He, Brandon Hernandez, Michael Iervese, Daniel Jadernas, Jesse Kappmeier, Kevin Keefe, Collin Knight, Brandon Miller, Scott Moore, Daniel Murray, Steven Swanson, Kevin Tolman, Karen Wright...and many more

Topics

- IMCL Facility Design and Performance
- Shielded Cell Design and Performance
- IMCL Shielded Transfer Cask Design and Performance
- Current IMCL Capabilities
- Future IMCL Capabilities
- Looking Forward

IMCL Concept (2008)




- Idea first presented in 2008 to support Nuclear Science User Facility
- Micro XRD, EPMA, IASCC, FIB, mechanical testing, and TEM

IMCL Design Goals

- Meet DOE and industry program needs
- Broadly accessible as a national/international user facility
- Routine application of state-of-the-art microstructural characterization capability for analysis of irradiated nuclear fuels and materials
- Reduce (dramatically) the time required to complete PIE of irradiated fuels and materials
- Reconfigurable over 40+ year lifetime
- High material quantity limits

IMCL Facility Design (2010)



- 1,130 m² total area
 - 750 m² open bay laboratory
 - 380 m² mechanical and office space
- Single pour reinforced concrete floor 45 cm thick
 - Vibration isolation pads near each instrument 15 cm thick
 - Mechanical room on separate foundation
- Reinforced concrete walls (seismic PC-3)
- Single HEPA filtered ventilation system serves HVAC and instrument needs
- IMCL is a Hazard Category II nuclear facility with a material envelope of 300 Ci ²³⁹Pu equivalent (3.4 g ²⁴⁴Cm)
- 700 g ²³⁹Pu from perspective of criticality

IMCL in 2015



- IMCL building construction was completed in August 2012
- Instrument cell installation began in 2016





IMCL FIB and TEM were heavily used during TPC construction

IMCL Facility Performance


- Facility design based on vibration, EMI, temperature stability, and acoustic noise criteria required for high-resolution TEM
- ✓ Vibrational performance of facility well within instrument specifications
 - All instruments installed with active vibration cancelling systems to protect against occasional transient vibration (heavy trucks)
- ✗ Acoustic noise higher than instrument specification
 - Noise level above 55 dB below 2 kHz caused by ventilation system
 - Slight impact on instrument performance
 - Some impact on human performance
- Asynchronous electromagnetic noise slightly out of limits
- Temperature stability in open bay insufficient for TEM (but TEM room required anyway)
- Lesson learned:
 - Isolate room HVAC from hot cell ventilation system if possible (but this is costly)
 - Safety basis/operational tradeoffs

Shielded Cell Design Concept (2010)




- Conventional concrete cell ~1 m (3') wall thickness with removable steel front and back walls and rear entry door
- Typical of 1960's cell design currently in use in U.S.
- Difficult to maintain modern instruments using this type of cell

Final Shielded Cell Design



- Shielding and confinement boundaries are separated for ease of access to instrument
- Inert glovebox provides containment of $\alpha + \beta$ contamination
- 22 cm (8.5") thick steel γ shield walls
- Lead glass windows
- Manipulators penetrate glovebox front wall
- No roof on cells
 - Simplify installation of piping, electrical, and instrumentation
 - Seismic issues

Final Shielded Cell Design



- Instrument connected to glovebox with reinforced 'rubber' bellows
- Instrument is part of $\alpha + \beta$ confinement boundary
- Access to glovebox interior through back glove wall
- Commercial (unshielded) entry door used to control access; labyrinth provides adequate shielding
- Instrument electronics/detectors are not 'hardened'
- Shielded sample storage in glovebox


Shielded Cell Design



Shielded Cell Installation





- Overhead crane not included in facility design (affordability)
- Shield panels (3~4 MT) installed using 20 ton mobile crane
- Future cell reconfiguration will require portable gantry crane




FIB Loading System


- Instrument loading through custom sample transfer system



FIB Loading System




Shielding Performance



- 0.9 Ci ^{60}Co source testing
- Contact dose rate at front face $5 \mu\text{S/hr}$ ($< 0.5 \text{ mrem/hr}$) per hour below 1.8 m (6 ft) height
- Absence of roof leads to slightly higher dose rates $20 \mu\text{S/hr}$ (2 mrem/hr) above 1.8 m
- General area dose rate on roof is $200 \mu\text{S/hr}$ (20 mrem/hr) – access control

Shielded Transfer Container



- Cask mates to back wall of glovebox
- Clean rapid transfer port (alpha/beta port) is mechanically interlocked to mating port on the cask. Neither container nor glovebox port will open unless the container is 'locked' to the glovebox
- Lightly shielded transfer containers also used

Shielded Transfer Container



- Shielded Transfer Container (STC) mates to shielded instrument cells, Shielded Sample Preparation Area, and air hood
- 100 cm (4 ") of lead shielding
- Interior cavity ~10 cm dia. x 25 cm long
- Total weight ~1950 kg
- Hydraulic adjustment of STC height to match shielded cell cask stand height
- Will interconnect with HFEF (Hot Fuel Examination Facility, 2019) and SPL (Sample Preparation Laboratory)
- Not qualified for use on public roadways

Shielded Transfer Container Performance

ALL 3


Survey #: M-20170331-12

Di



- IMCL Shielded Transfer Container in position on the SSPA (Shielded Sample Preparation Area)
- Goal: $< 2000 \mu\text{S/hr}$ at 30 cm ($< 200 \text{ mrem/hr}$) with 2 Ci ^{60}Co source term
- Contact dose rate on surface $500 \mu\text{S/hr}$ (50 mrem/hr) with 1.8 Ci ^{60}Co source term
- One occurrence of alpha port sticking closed in several hundred uses

IMCL Capabilities



Fully operational

In progress

Procured, awaiting installation

Future expansion

SSPA – Shielded Sample Preparation Area
 EPMA – Electron Probe MicroAnalysis
 FIB – Focused Ion Beam
 TEM – Transmission Electron Microscope
 TPTC – Thermal Properties Test Cell


Shielded Sample Preparation Area



- Shielded sample preparation
 - Diamond saw
 - Autopolisher
- Optical microscopy
 - Keyence VHX
- Sample transfer cell between shielded box and glovebox
- Glovebox for preparation of reduced size/low dose rate samples
- Hood for transfer of low dose rate samples, waste
- Lessons: Argon atmosphere, waste handling



Operational in August 2017

Electron Probe MicroAnalysis (EPMA)




EPMA analysis of
a full cross
section of
irradiated U-Pu-
Am-Np-Zr fuel


Operational in
August 2017




Transmission Electron Microscopy



Titan 200 KeV TEM with ChemiSTEM EDS system.
Operational in March 2017




Top: Microstructure of MOX fast reactor fuel irradiated to 112 GWd/tHM. Bottom: Atomic resolution imaging of 5 metal precipitates and fission gas bubbles in UO_2 .




Dual Beam Focused Ion Beams



- FEI Quanta Ga FIB
- FEI Helios Xe plasma FIB
- Lessons:
 - Sample transfer system
 - Cable lengths may impact performance
 - Helios has short working distance and in-lens detectors



Microtensile testing of U-Mo fuel at 500°C.



Inverse pole figure map of irradiated U-Mo showing the formation of a fine grain (240 nm) structure. Surface cleaned with Helios P-FIB


Operational March 2018

Thermal Properties Cell



- Shielded cell construction complete
- Currently in final acceptance testing
- Largest cell in IMCL
- Instruments:
 - Laser flash thermal diffusivity
 - Thermal conductivity microscope
 - Thermogravimetric Analysis, Differential Scanning Calorimetry, Mass Spectrometry
- Operational for radiological samples June 2019

Additional IMCL Capabilities



Currently installed

In progress

Procured, awaiting installation

Future expansion – user specified

SSPA – Shielded Sample Preparation Area
 EPMA – Electron Probe MicroAnalysis
 FIB – Focused Ion Beam
 TEM – Transmission Electron Microscope
 TPTC – Thermal Properties Test Cell

Additional Capabilities



- Quantum systems
Dynacool-9 PPMS
- 2 - 400 K
 - 9 Tesla field
 - Electrical, magnetic, and thermal property measurements
 - January 2019




- Zeiss Versa 520
- 0.7 μm spatial resolution
 - Diffraction contrast tomography
 - In-situ heating and mechanical testing
 - Flat panel detector
 - March 2019



- Bruker D-8 μ -XRD, 50 μm resolution
- Panalytical Empyrean powder XRD with heated stage
- Unshielded
- Currently installed

- Installation of probe corrector and EELS on Titan TEM (March 2019)
- JEOL-7600 FEG-SEM transferred from another facility (March 2019)
- One shielded and one unshielded space remain for future instruments

Looking Forward



- National and international workshops in 2011 defined needs for postirradiation examination.
- A combination of the Hot Fuel Examination Facility, Sample Preparation Laboratory, and the Irradiated Material Characterization Laboratory will meet those needs.



Come work with us!

mittchell.meyer@inl.gov
(208) 589-2958